



ELECTRONIC TEST:

1. ALL CABLE 100% TEST, OPEN ,SHORT,MISS WIRE
2. RESISTANCE: 2.0 ohm max
3. I. RESISTANCE: 10M ohm min
4. HI-POT: 300V DC/10ms
5. DEMEMSIONS MARK” ◀ ”SHOULD BE CHECKED;

P1	P2
1	OPEN
2	RED
3	BLACK
4	BLACK
5	BLACK
6	BLACK
7	BLACK
8	BLACK
9	BLACK
10	BLACK
11	BLACK
12	BLACK
13	YELLOW
14	YELLOW
15	YELLOW

PIN ASSIGNMENT

NO.	PART NO.	DESCRIPTION	Q'TY	UNIT
⑦	TERMINAL	SM 2510T	4	PCS
⑥	HOUSING	SM 2510H-04 PITCH:2.54mm WHITE	1	PC
⑤	011-06000-020	SATA 15P IDC TYPE	1	PC
④	209-13230-000	S-ATA-15P ,BLACK G/F IDC TYPE	1	PC
③	101-34018-030	UL1007 18AWG BLACK 125mm	2	PCS
②	101-34418-040	UL1007 18AWG YELLOW 125mm	1	PC
①	101-34218-040	UL1007 18AWG RED 125mm	1	PC

項目 ITEM	設 變 內 容	DESCRIPTION	日期 DATE
①			
②			
③			



CP User 坤紀企業股份有限公司  
COMPONENT USER INDUSTRY CO., LTD

項目	設 變 內 容	DESCRIPTION	日期 DATE
①			
②			
③			