



ELECTRONIC TEST:

1. ALL CABLE 100% TEST, OPEN ,SHORT, MISS WIRE
2. RESISTANCE: 2.0 ohm max
3. I.RESISTANCE: 10M ohm min
4. HI-POT: 300V DC/10ms
5. DIMENSIONS MARK" " SHOULD BE CHECKED;

PIN ASSIGNMENT

P1/P2	P2
15	1 YELLOW
14	
13	
12	2 BLACK
11	
10	
9	
8	4 RED
7	
6	
5	3 BLACK
4	
3	
2	
1	OPEN

NO.	PART NO.	DESCRIPTION	Q'TY	UNIT
⑧	SATA	SATA 15P 參A 邊蓋	1	Pc
⑦	SATA	SATA 15P 參A 的蓋	1	Pc
⑥	TERMINAL	CONTACT NI FLESH MALE	4	Pcs
⑤	HOUSING	POWER-4P HOUSING FEMALE, WHITE	1	Pcs
④	HOOK UP WIRE	UL1007 18AWG YELLOW 290mm	1	Pcs
③	HOOK UP WIRE	UL1007 18AWG BLACK 290mm	2	Pcs
②	HOOK UP WIRE	UL1007 18AWG RED 290mm	1	Pcs
①	SATA CONN	S-ATA-15P ,BLACK G/F 參A	2	Pcs

項目 ITEM	設 變 內 容	DESCRIPTION	日期 DATE
①			
②			
③			



CP User 坤紀企業股份有限公司
COMPONENT USER INDUSTRY CO., LTD

項目	日期	圖名	圖號	料號	頁數	版本
總圖者 DRAW BY	2007.11.22	SATA 15P CABLE			1/1	2.0
核對者 CHECK BY						
核准者 APPROVED BY						