

⑩	SATA 刺破式边盖	SATA 15P 刺破式边盖	2	Pos
⑨	SATA CONN	S-ATA-15P ,BLACK G/F 刺破式	2	Pos
⑧	HOOK UP WIRE	UL1007 18AWG RED 155mm	1	Pos
⑦	HOOK UP WIRE	UL1007 18AWG BLACK 155mm	2	Pos
⑥	HOOK UP WIRE	UL1007 18AWG YELLOW 155mm	1	Pos
⑤	HOOK UP WIRE	UL1007 18AWG RED 175mm	1	Pos
④	HOOK UP WIRE	UL1007 18AWG BLACK 175mm	2	Pos
③	HOOK UP WIRE	UL1007 18AWG YELLOW 175mm	1	Pos
②	TERMINAL	CONTACT Ni FLESH MALE	4	Pos
①	HOUSING	POWER-4P FEMALE, WHITE	1	Pc

NO.	PART NO.	DESCRIPTION	Q'TY	UNIT
-----	----------	-------------	------	------


**ELECTRONIC TEST:**

- 1.ALL CABLE 100% TEST,OPEN ,SHORT,MISS WIRE
- 2.RESISTANCE:2.0 ohm max
- 3.1.RESISTANCE:10M ohm min
- 4.HI-POT:300V DC/10ms

P1	P2	COLOR	P3
15	1	YELLOW	15
14	2	BLACK	14
13	3	BLACK	13
12	4	RED	12
11	5	RED	11
10	6	BLACK	10
9	7	BLACK	9
8	8	BLACK	8
7	9	BLACK	7
6	10	BLACK	6
5	11	BLACK	5
4	12	BLACK	4
3	13	BLACK	3
2	14	BLACK	2
1	15	BLACK	1
		OPEN	

PIN ASSIGNMENT

項目	變更內容	日期
ITEM	DESCRIPTION	DATE
①		
②		
③		


**CP User 坤紀企業股份有限公司**  
 COMPONENT USER INDUSTRY CO., LTD

繪圖者 DRAW BY	MICHELL郭	一般公差 X:±	比例 SCALE	NOVE	圖名 DESCRIPTION	SATA 15P CABLE
核對者 CHECK BY		單位 UNIT	舊料號	D:\	圖號 DVG. NO	9610004-2
核准者 APPROVED BY		mm	儲位 CMP QND		料號 BOM. NO	3030299004
日期 DATE	2007.10.8				頁數 PAGE	1/1
					版次 REV (QND)	2.0

QP-F-01-8