



ELECTRONIC TEST:

1. ALL CABLE 100% TEST, OPEN ,SHORT, MISS WIRE
2. RESISTANCE: 2.0 ohm max
3. I. RESISTANCE: 10M ohm min
4. HI-POT: 300V DC/10ms
5. DIMENSIONS MARK" ◀ "SHOULD BE CHECKED;

P1	P2
1	OPEN
2	BLACK
3	BLACK
4	BLACK
5	BLACK
6	BLACK
7	BLACK
8	BLACK
9	BLACK
10	BLACK
11	BLACK
12	BLACK
13	BLACK
14	BLACK
15	YELLOW

PIN ASSIGNMENT

NO.	PART NO.	DESCRIPTION	Q'TY	UNIT
①		HOUSING	1	Pcs
②		TERMINAL	4	Pcs
③		HOOK UP WIRE	1	Pcs
④		HOOK UP WIRE	2	Pcs
⑤		HOOK UP WIRE	1	Pcs
⑥		SATA CONN	1	Pcs
⑦		INNER MOLDING	0.0009	KG
⑧		OVER MOLDING	0.0027	KG

項目 ITEM	設 變 內 容 DESCRIPTION	日期 DATE
①		
②		
③		

項目 ITEM	設 變 內 容 DESCRIPTION	日期 DATE
①		
②		
③		

坤紀企業股份有限公司  
 CP User COMPONENT USER INDUSTRY CO., LTD

總圖者 DRAW BY	MICHELLE郭	一般公差 差 X.X±	比例 SCALE	NOVE	圖名 DESCRIPTION	SATA 15P / 4P FEMALE
核對者 CHECK BY		單位 UNIT	舊圖號		圖號 DWG. NO	CSP-15PRB4P
核准者 APPROVED BY		mm	舊料號		料號 BOM. NO	
日期 DATE	2007.5.04		備位 CMP (IND)	D: \	頁數 PAGE	1/1
					版次 REV (IND)	2.0