


ELECTRONIC TEST:

1. ALL CABLE 100% TEST, OPEN , SHORT, MISSWIRE
2. RESISTANCE: 2 ohm max
3. I. RESISTANCE: 10M ohm min
4. HI-POT: 500V DC/10ms
5. DIMENSIONS MARK" ◀ " SHOULD BE CHECKED;




P1	P2
15	1
14	1
13	2
12	2
11	3
10	3
9	4
8	4
7	4
6	4
5	3
4	3
3	3
2	3
1	OPEN

PIN ASSIGNMENT

NO.	PART NO.	DESCRIPTION	Q'TY	UNIT
⑦	SATA 15P 上蓋	SATA 15P 上蓋 COLOR:BLACK	1	Pc
⑥	SATA CONN	S-ATA-15P .BLACK MOLDING 1U" ASSEMBLY TYPE	1	Pc
⑤	HOOK UP WIRE	UL1007 18AWG YELLOW 190mm	1	Pc
④	HOOK UP WIRE	UL1007 18AWG BLACK 190mm	2	Pcs
③	HOOK UP WIRE	UL1007 18AWG RED 190mm	1	Pc
②	TERMINAL	CONTACT Ni FLESH MALE	4	Pcs
①	HOUSING	POWER-4P FEMALE, WHITE	1	Pc

項目	設備內容	DESCRIPTION	日期
①			
②			
③			


**坤紀企業股份有限公司**  
 COMPONENT USER INDUSTRY CO., LTD

繪圖者	一般公差	比例	圖名
DRRAW BY	X: X±0.5	SCALE	DESCRIPTION
核對者	單位	NOVE	SATA POWER CABLE
CHECK BY	mm		
核准者	備位		
APPROVIN	備料號		
日期	圖號		
DATE	DWG. NO		
2008.10.31	3030200002		
	料號		
	BOM. NO		
	頁數		
	PAGE		
	1/1		
	版次		
	REV. NO		
	2.0		

QP-F-01-8