



**ELECTRONIC TEST:**

1. ALL CABLE 100% TEST, OPEN ,SHORT, MISSWIRE
2. RESISTANCE: 2 ohm max
3. I. RESISTANCE: 10M ohm min
4. HI-POT: 300V DC/10ms
5. DIMENSIONS MARK "▲" SHOULD BE CHECKED;

P1	P2
15	1
14	1
13	2
12	2
11	3
10	3
9	4
8	4
7	4
6	3
5	3
4	3
3	3
2	3
1	OPEN

PIN ASSIGNMENT



NO.	PART NO.	DESCRIPTION	Q'TY	UNIT	
⑨		OVER MOLDING	45P PVC COLOR:BLACK	0.0025	Kg
⑧		INNER MOLDING	35P PVC COLOR:BLACK	0.0022	Kg
⑦		SATA15P LATCH	S-ATA-15P LATCH	1	Pc
⑥		SATA CONN	S-ATA-15P WITH LATCH:BLACK MOLDING G/F	1	Pc
⑤		HOOK UP WIRE	UL1007 18AWG YELLOW 115mm	1	Pc
④		HOOK UP WIRE	UL1007 18AWG BLACK 115mm	2	Pcs
③		HOOK UP WIRE	UL1007 18AWG RED 115mm	1	Pc
②		TERMINAL	CONTACT Ni FLESH MALE	4	Pcs
①		HOUSING	POWER-4P FEMALE, WHITE	1	Pc

項目	設 變 內 容	日 期
ITEM	DESCRIPTION	DATE
1		
2		
3		

<p>坤紀企業股份有限公司 CP. User Component User Industry Co Ltd</p>		繪圖者 DRAW BY	MCHELL	一般公差 X: X±0.5	比例 SCALE	NOVE	圖名 DESCRIPTION	SATA POWER CABLE
核對者 CHECK BY	核准者 APPROVAL	日期 DATE	2008.6.06	單位 UNIT	儲位 CMP (NO)	D: \	圖號 DWG. NO	CSP-15PVLB4P
日期 DATE	2008.6.06	儲位 CMP (NO)	D: \	頁數 PAGE	1/1	版次 REV (NO)	2.0	

QP-F-01-8