



ELECTRONIC TEST:

1. ALL CABLE 100% TEST, OPEN, SHORT, MISS WIRE
2. RESISTANCE: 2.0 ohm max
3. RESISTANCE: 10M ohm min
4. HI-POT: 300V DC/10ms
5. DIMENSIONS MARK "▲" SHOULD BE CHECKED;

PIN ASSIGNMENT

P1/P2	P2
15	1 YELLOW
14	1 YELLOW
13	1 YELLOW
12	2 BLACK
11	2 BLACK
10	2 BLACK
9	2 BLACK
8	4 RED
7	4 RED
6	3 BLACK
5	3 BLACK
4	3 BLACK
3	3 BLACK
2	3 BLACK
1	OPEN

NO.	PART NO.	DESCRIPTION	Q'TY	UNIT
⑩	SATA	SATA 15P COLOR:BLACK	1	Pc
⑨	SATA CONN	S-ATA-15P ,BLACK 1U" ASSEMBLY TYPE	1	Pc
⑧	SATA	SATA 15P	1	Pc
⑦	G 網壳胶牙	堵帽 L=25mm	1	Pc
⑥	TERMINAL	CONTACT NI FLESH MALE	4	Pcs
⑤	HOUSING	POWER-4P HOUSING FEMALE, WHITE	1	Pcs
④	HOOK UP WIRE	UL1007 18AWG YELLOW 290mm	1	Pcs
③	HOOK UP WIRE	UL1007 18AWG BLACK 290mm	2	Pcs
②	HOOK UP WIRE	UL1007 18AWG RED 290mm	1	Pcs
①	SATA CONN	S-ATA-15P ,BLACK G/F	1	Pcs

項目 ITEM	設 變 內 容	日期 DATE	變更內容	日期 DATE	圖名 DESCRIPTION	圖號 DWG. NO.	料號 BOM. NO.	頁數 PAGE	版次 REV. (NO)
△1					SATA 15P CABLE	CSP-15PV12B4P		1/1	2.0
△2									
△3									


 坤紀企業股份有限公司
 CP User
 COMPONENT USER INDUSTRY CO., LTD

繪圖者 DRAW BY	一般公差 X.X±	比例 SCALE	圖名 DESCRIPTION
MICHELLE郭		NOVE	SATA 15P CABLE
核對者 CHECK BY	單位 UNIT	圖號 DWG. NO.	料號 BOM. NO.
	mm	9608006	
日期 DATE	審核者 APPROVED BY	儲位 OHP (NO)	頁數 PAGE
2007. 8. 02		D: \	1/1