



**ELECTRONIC TEST:**

1. ALL CABLE 100% TEST, OPEN, SHORT, MISS WIRE
2. RESISTANCE: 2.0 ohm max
3. RESISTANCE: 20M ohm min
4. HI-POT: 200V DC/10ms
5. DIMENSIONS MARK "▼" SHOULD BE CHECKED;

⑥	G101-4500-300	45P PVC CCLOR:BLACK	0.0065	KG
⑤	G101-3500-300	35P PVC CCLOR:BLACK	0.007	KG
④	G100-0019-300	PE	0.005	KG
③	GSS30-1503-00	S-ATA15P „BACK MOLDING 3U“	1	PC
②	TERMINAL	TER:851-PS ID:2.1mm L=16.5mm	4	PCS
①	CABLE	UL2464 22AWG*4C+AL+BRAID OD:5.5mm BLACK	485	mm
NO.	PART NO.	DESCRIPTION	Q'TY	UNIT

項目 ITEM	設 變 內 容 DESCRIPTION	日期 DATE
⚠		
⚠		
⚠		


**坤紀企業股份有限公司**  
 COMPONENT USER  
 INDUSTRY CO.,  
 LTD

繪圖者 DRAW BY	MICHELLE 邱	一般公差 SCALE	X.X±	比例 SCALE	NOVC	圖名 DESCRIPTION	SATA 15P 接 大四P母	
校對者 CHECK BY		單位 UNIT	mm	繪圖號		圖號 DWG. NO	9510003	
校核者 APPROV		價位 PRICE		物料號		料號 SOHL NO	3132299009	
日期 DATE	2007/01/16	頁數 PAGE	1/1	版本 REV NO	2.0			