

ELECTRONIC TEST:

1. ALL CABLE 100% TEST, OPEN, SHORT, MISSWIRE

2. RESISTANCE: 2 ohm max


3. RESISTANCE: 10M ohm min

4. HI-POT: 500V DC/10ms

5. DIMENSIONS MARK "▲" SHOULD BE CHECKED;

NO.	PART NO.	DESCRIPTION	Q'TY	UNIT		
⑤		OVER MOLDING	45P PVC COLOR:BLACK	CMB05093	0.0054	Kg
④		INNER MOLDING	35P PVC COLOR:BLACK	CMB05092	0.0047	Kg
③		SATA LATCH	SATA 7P SHORT LATCH		2	pcs
②		SATA CABLE	7P SERIAL ATA CABLE 26AWG COLOR:RED OD:2.20*7.80±0.20mm (UL2725 OR UL21149)		100	mm
①		SATA CONN	S-ATA-7P BLACK MOLDING G/F WITH LATCH		2	pcs

項目 ITEM	設 變 內 容	DESCRIPTION	日期 DATE
①			
②			
③			


 CP User 坤紀企業股份有限公司
 COMPONENT USER INDUSTRY CO., LTD

繪圖者 DRAW BY	MICHELLE郭	一般公差	比例 SCALE	NOTE	圖名 DESCRIPTION	S-ATA CABLE ASS'Y
核對者 CHECK BY		X.Y±	舊圖號		圖號 DWG. NO	CSA-RLRL
核准者 APPROVED BY		UNIT	舊料號		料號 BOM. NO	
日期 DATE	2008.6.12	mm	儲位 CMP (NO)	D:\	頁數 PAGE	1/1
					版本 REV (NO)	x1