



1. ELECTRICAL:
- 1.1 100% CONTINUITY TEST
  - 1.2 INSULATION RESISTANCE: 10 MEGA OHMS MIN.
  - 1.3 HI-POT: DC300V/0.01S
  - 1.4 CONTACT RESISTANCE: 2.0 OHMS MAX.

③	OUTER MOLD	45P PVC COLOR:BLACK	A/R	9
②	USB CABLE	USB2.0 2725 28#/1P+24#/2C+4AEB OD=4.5MM BLACK	2000	mm
①	USB CONN	USB A TYPE MALE WHITE PIN GOLD PLATED G/F LONG SOLDER TYPE	2	Set
NO.	PART NO.	DESCRIPTION	Q'TY	UNIT

項目	設 變 內 容	DESCRIPTION	日期	DATE
①				
②				
③				

  

繪圖者 DRAW BY	MCHELL鄧	一般公差 X.X±0.3	比例 SCALE	NOVE	圖名 DESCRIPTION	USB AM TO USB BM CABLE ASSY
核對者 CHECK BY		單位 UNIT	備料號 料號		圖號 DVG. NO	9708015
核准者 APPROVED BY		mm	備位 CMP. QND	D:\	料號 BDM. NO	
日期 DATE	2008.8.22				頁數 PAGE	1/1
					版次 REV. QND	2.0

CP. User  
坤紀企業股份有限公司  
COMPONENT USER INDUSTRY CO., LTD