



NOTES:

1. ALL CABLE 100% TEST, OPEN , SHORT, MISS WIRE
2. RESISTANCE: 2.0 ohm max
3. I. RESISTANCE: 20M ohm min
4. HI-POT: 200V DC/10ms
5. DIMENSIONS MARK" ◀ "SHOULD BE CHECKED

①	外覆料	4SP PVC COLOR: BLACK	A/R	KG
②	內覆料	PE	A/R	KG
③	熱縮套管	∅1.5*8 COLOR: BLACK	1	PC
④	線母	H-AUT 5.4*2.3 M3*P0.5	2	PCS
⑤	USB A TYPE	USB A TYPE(MALE) G/F WHITE	1	PC
⑥	USB CONN	USB A TYPE(FEMALE) 4P 180 ° INSULATION: WHITE 鍍金 G/F	1	PC
⑦	USB CABLE	USB 2.0 CABLE 28AWG*1P+26AWG*2C+AE8 JACKET COLOR: BLACK OD: 3.8mm	480	mm

項目	變 容	內 容	DESCRIPTION	日期	DATE
1					
2					
3					



坤紀企業股份有限公司
Component User Industry Co Ltd

繪圖者 DRAW BY	MCHELL 郭	一般公差 X.X±0.3	比例 SCALE	NOVE	圖名 DESCRIPTION	USB AF/USB AM CABLE ASSY
核對者 CHECK BY		單位 UNIT	備料號		圖號 DWG. NO	CUSB-AMAF
核准者 APPROVE BY		mm	儲位 DWP (NO)	D: \	料號 BOM. NO	
日期 DATE	2008.4.09				頁數 PAGE	1/1
					版次 REV (NO)	2.0

QP-F-01-8