


1. DIMENSIONS MARK"▼"SHOULD BE CHECKED;
2. 100% OPEN SHORT & MISWIRE TEST
3. ELECTRIC FEATURE:COND:2 ohm /MAX;
I.R:10M ohm,AT DC 300V

PIN ASSIGNMENT

P1(a)	P2(a)	P1(b)	P2(b)
1 Drain 1	1	1	1
2	2	2	2
3	3	3	3
4 Drain 2	4	4	4
5	5	5	5
6	6	6	6
7 Drain 3	7	7	7
		8	8
		9	9
		10	10
		11	11
		12	12
		13	13
		14	14
		15	15

NO.	PART NAME.	DESCRIPTION	Q'TY	UNIT
⑦	22P CONN	S-ATA22P FEMALE BLACK MOLDING G/F 脚压式 带尖点 有凸	2	Pcs
⑥	CABLE	UL21149 7C SATA7P CABLE 26AWG RED 2.2*7.8±0.20mm	A/R	mm
⑤	WIRE	UL1007 20AWG YELLOW	1	Pcs
④	WIRE	UL1007 20AWG BLACK	2	Pcs
③	WIRE	UL1007 20AWG RED	1	Pcs
②	PVC	45P PVC BLACK	0.017	KG
①	PE	PE	0.008	KG

項目 ITEM	設 變 內 容 DESCRIPTION	日期 DATE	繪圖者 DRAW BY	一般公差 X.X±0.3	比例 SCALE	圖名 DESCRIPTION	S-ATA CABLE ASS'Y
①			核對者 CHECK BY		圖號 DWG NO	9709027	
②			核對者 APPROVED BY	單位 UNIT	舊料號	料號 BOM NO	
③			日期 DATE	mm	儲位 CMP QND	頁數 PAGE	1/1
			2008.9.25		D:\	圖號 DWG NO	REV QND
						頁數 PAGE	2.0


 CP User 坤紀企業股份有限公司
 COMPONENT USER INDUSTRY CO., LTD