


- NOTES:
1. DIMENSIONS MARK"▲"SHOULD BE CHECKED;
 2. 100% OPEN SHORT & MISWIRE TEST
 3. ELECTRIC FEATURE:COND:2 ohm /MAX;
I.R:10M ohm,AT DC 300V

項目 ITEM	設 變 內 容 DESCRIPTION	日期 DATE
1		
2		
3		


 CP User 坤紀企業股份有限公司
 COMPONENT USER INDUSTRY CO., LTD

NO.	PART NAME.	DESCRIPTION	圖名 DESCRIPTION	圖號 Dwg. No.	料號 BDM No.	頁數 PAGE	版次 REV. (AND)
⑧	22P CONN	S-ATA22P FEMALE BLACK MOLDING G/F	綁壓式 帶發點 有凸				
⑦	22P CONN	S-ATA22P MALE BLACK MOLDING G/F	綁壓式 無尖點				
⑥	CABLE	UL21149 7C SATA7P CABLE 26AWG RED 2.2*7.8±0.20mm					
⑤	WIRE	UL1007 20AWG YELLOW					
④	WIRE	UL1007 20AWG BLACK					
③	WIRE	UL1007 20AWG RED					
②	PVC	45P PVC BLACK					
①	PE	PE					

繪圖者 DRAW BY	核對者 CHECK BY	核准者 APPROVED BY	日期 DATE
MCHELL			2008.10.6

一般公差 X.X±0.3	比例 SCALE	NOVE	圖名 DESCRIPTION	圖號 Dwg. No.	料號 BDM No.	頁數 PAGE	版次 REV. (AND)
			S-ATA CABLE ASS'Y	9709030		1/1	2.0